

Sikagard® Natural Look Clear Sealer

Water-repellent sealer

Construction

Description	Sikagard Natural Look Sealer is a commercial-grade water-repellent sealer that penetrates an absorbent surface to form a seal against the elements such as water and chlorides.
Where To Use	Sikagard Natural Look Sealer water repellent sealer can be used on concrete, masonry, mortar, brick and stone.
Advantages	<ul style="list-style-type: none">■ Will not alter the appearance of your surface■ Improves resistance to dirt penetration■ Reduces the growth of fungi and moss■ For vertical and horizontal applications■ Protects against freeze-thaw damage
Coverage	1 gallon jug covers 100 – 250 sq. ft, depending on porosity of substrate.
Packaging	1 gallon jug
How to Use	
Surface Preparation	Surface must be clean, sound, dust-free and dry. Remove all dust, dirt, loose concrete, grease, curing compounds, paint and other particles by mechanical means (i.e. pressure wash, blast clean, etc.).
Mixing	Shake product thoroughly before applying.
Application	Apply to surface by brushing, rolling or spraying over entire area moving in one direction uniformly. Avoid puddling of product in any area. A maximum of two coats may be required, depending on porosity of surface. Recommended application temperature is 45°-95°F (7°-35°C) ambient and substrate. Note: Preliminary site test application is recommended (preferably on a small, prepped, inconspicuous surface) to determine satisfactory appearance and surface slip resistance.
Limitations	<ul style="list-style-type: none">■ Substrate must be dry prior to application (minimum 48 hours)■ Do not apply if rain is in the forecast■ Cannot seal visible cracks. Repair all cracks or surface defects before sealing■ Do not use on concrete under 7 days old■ Avoid puddling; apply even coats■ Do not attempt to build up thickness■ Does not contain an antimicrobial additive

Typical Data (Material and curing conditions at 73°F (23°C) and 50% R.H.)

Shelf Life	1 year
Storage Conditions	Store dry at 45°-90°F (7-32°C). Keep from freezing. Condition material to 65-75°F (18-24°C) before using.
Color	Milky white when applied but dries clear
VOC	38.5 g/l
Dry Time	Approximately 4-8 hrs. Wait 24 hrs. before exposing to foot/car traffic. Approximately 72 hrs. for maximum water repellency, depending on surface and atmospheric conditions.

Caution	CAUTION: IRRITANT, SENSITIZER. Contains polymer emulsion (silane/siloxane mixture). May cause eye/skin/respiratory irritation. Prolonged and or repeated contact with skin may cause an allergic reaction/sensitization. May be harmful if swallowed. Deliberate concentration of vapors for purposes of inhalation is harmful and can be fatal.
Handling and Storage	Avoid direct contact. Wear personal protective equipment (chemical resistant goggles/gloves/clothing) to prevent direct contact with skin and eyes. Use only in well ventilated areas. Open doors and windows during use. Use a properly fitted NIOSH respirator if ventilation is poor. Wash thoroughly with soap and water after use. Remove contaminated clothing and laundry before reuse.
First Aid	Eyes: Hold eyelids apart and flush thoroughly with water for 15 minutes. Skin: Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. Inhalation: Remove to fresh air. Ingestion: Do not induce vomiting. Dilute with water. Contact physician. In all cases contact a physician immediately if symptoms persist.
Clean Up	Use personal protective equipment (chemical resistant gloves/ goggles/clothing). Without direct contact, remove spilled or excess product and placed in suitable sealed container. Dispose of excess product and container in accordance with applicable environmental regulations.

Refer to Material Safety Data Sheet for more information

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at www.sikausa.com or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at www.sikausa.com or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BELIEVABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Visit our website at www.sikausa.com

1-800-933-SIKA NATIONWIDE

Regional Information and Sales Centers. For the location of your nearest Sika sales office, contact your regional center.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225

Sika Canada Inc.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

Sika and Sikagard are registered trademarks.
Made in USA. Printed in USA.

