



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

SRW SS5

Product Specification

SRW Products Manufactures/Supplies a 100% Polypropylene, Woven fabric called SRW SS5 offering optimum performance when used in stabilization applications. Produced from first quality raw material, they provide the perfect balance of strength and separation. SRW SS5 meets AASHTO's M288-92 requirements for Class A and B Subsurface Drainage, Class A and B Erosion Control and Medium Survivability Separation Fabrics. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents.

SRW SS5 meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Grab Tensile	ASTM D 4632	lbs.	200
Grab Elongation	ASTM D 4632	lbs.	15
Trap Tear Strength	ASTM D 4533	lbs.	75
Puncture Strength	ASTM D 4833	lbs.	90
CBR Puncture	ASTM D-6241	lbs.	700
Mullen Burst	ASTM D 3786	Psi	400
Permittivity	ASTM D 4491	sec ⁻¹	0.05
Water Flow	ASTM D 4491	gpm/ft ²	5
UV Resistance	ASTM D 4355	% Strength Retained After 500 Hours	70
AOS	ASTM D 4751	US Sieve	#50

To the best of our knowledge, the information contained herein is accurate. However, SRW Products cannot anticipate all conditions under which SRW product information and our products or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of our products either alone or in combination with other products. Final determination of the suitability of any information or material for the use contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.